Application No.: 10/591,313 Filing Date: July 23, 2007

AMENDMENTS TO THE CLAIMS

- 1. **(Currently amended)** A dispersion comprising a thermoplastic cellulose polymer or a derivative thereof, a phthalate ester of a C₁-C₆ alkylated aromatic alcohol, an alkaline earth metal salt of a C₉-C₂₀ aliphatic fatty acid, a surfactant, a lower alkyl methacrylate polymer and further comprising one or more components selected from the group consisting of: a metal earbonate a white metal oxide, a solvent, wherein the dispersion adheres to a substrate selected from the group consisting of a plastic, a metal and a composite when applied to said substrate as part of a primera rust inhibitor and a lower alkyl methacrylate polymer.
- 2. **(Currently amended)** The dispersion of claim 1 <u>further comprising a white metal oxidelower alkyl methacrylate polymer.</u>
- 3. **(Currently amended)** The dispersion of claim <u>1,</u>2 wherein the lower alkyl methacrylate polymer is an ethyl methacrylate polymer.
- 4. **(Currently amended)** The dispersion of claim 1 <u>further comprising</u> a metal carbonate[[,]] <u>and</u> a white metal oxide, a <u>lower alkyl methacrylate polymer and a solvent</u>.
- 5. **(Currently amended)** The dispersion of claim 1 <u>further comprising</u> a metal carbonate, a white metal oxide, a lower alkyl methacrylate polymer, a solvent and a rust inhibitor.
 - 6. **(Original)** The dispersion of Claim 1 in a solid form.
 - 7. **(Original)** The dispersion of Claim 4 in a solid form.
 - 8. **(Original)** The dispersion of Claim 5 in a solid form.
 - 9. **(Original)** The dispersion of Claim 6 in a granulated form.
 - 10. **(Original)** The dispersion of Claim 7 in a granulated form.
 - 11. **(Original)** The dispersion of Claim 8 in a granulated form.
 - 12. **(Original)** A primer comprising the dispersion of Claim 1 and, a primer solvent.
- 13. (Original) The primer of claim 12 further comprising one or more components selected from the group consisting of: a C_1 - C_6 ketone, a C_1 - C_6 ester, a polymeric plasticizer and a halogenated, polyolefin.
- 14. **(Original)** The primer of claim 13 further comprising one or more components selected from the group consisting of: an alcohol, a polyhydroxy magnesium silicate derivate, and a silicon dioxide powder.

Application No.: 10/591,313 Filing Date: July 23, 2007

- 15. **(Original)** A primer comprising a primer solvent, a lower alkyl methacrylate polymer, a C_1 - C_6 ketone, a C_1 - C_5 ester, a phthalate ester of a C_1 - C_6 alkylated aromatic alcohol, a polymeric plasticizer, a halogenated polyolefin and the dispersion of claim 4.
 - 16. **(Original)** The primer of claim 15 further comprising the dispersion of claim 5.
- 17. **(Original)** The primer of claim 15 further comprising an alcohol, a thermoplastic cellulose polymer or a derivative thereof, a polyhydroxy magnesium silicate derivate and a silicon dioxide powder.
 - 18. (Currently amended) A method of manufacturing a primer including the steps of: mixing a first primer solution comprising a primer solvent and a lower alkyl methacrylate polymer in a first vessel;

mixing a second primer solution comprising the dispersion of claim 6 in a second vessel; and

mixing the first primer solution and the second primer solution together to form the primer;

wherein the primer adheres to a plastic, a metal and/or a composite substrate.

19. **(Currently amended)** A method of manufacturing a primer comprising:

mixing a first primer solution comprising a primer solvent and a lower alkyl methacrylate polymer;

mixing a second primer solution comprising a C_1 - C_6 ketone, a C_1 - C_6 ester, a phthalate ester of a C_1 - C_6 alkylated aromatic alcohol, and the dispersion of claim 7; and

mixing the first primer solution and the second primer solution together with a primer solvent, a C_1 - C_6 ketone, C_1 - C_6 ester, a polymeric plasticizer and a halogenated polyolefin to form the primer;

wherein the primer adheres to a plastic, a metal and/or a composite substrate.

- 20. **(Original)** The method of manufacturing a primer of claim 19 wherein the second primer solution comprises the dispersion of claim 8.
 - 21. (Previously presented) A method for coating a surface of an article comprising:

coating the surface with an adhesion promoter comprising an aromatic hydrocarbon, a co-polymer of a C_2 - C_6 alkene and a vinyl ester and a chlorinated polyolefin; and

coating the surface with the primer of claim 12 or claim 15.

Application No.: 10/591,313 Filing Date: July 23, 2007

- 22. (Previously presented) An article coated with the primer of claim 12 or claim 15.
- 23. **(New)** The dispersion of claim 1 further comprising one or more component selected from the group consisting of: a metal carbonate; a white metal oxide and a rust inhibitor.
- 24. **(New)** The dispersion of claim 1 wherein the dispersion adheres to a substrate selected from the group consisting of a polyethylene, a polypropylene, a polystyrene, a thermoplastic elastomer and an etheylene propylene rubber when applied to said substrate as part of a primer.